

MATERIAL SAFETY DATA SHEET  
according to 1907/2006/EC, Article 31

FEYCO  
TREFFERT

2830809

Reviewed on: 05.09.2016

Printing date: 05.09.2016

## SECTION 01: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- *Trade name:*  
THINNER V1664 FOR CASANIN WOOD PUTTY
- Article number / Safety Data Sheet:  
V16640
- *1.2 Relevant identified uses of the substance or mixture and uses advised against*
- Application of the substance / the preparation  
Coating material
- **1.3 Details of the supplier of the safety data sheet**
- *Manufacturer/Supplier:*  
FEYCO AG  
Hauptsitz  
Industriestrasse 11  
CH-9430 St. Margrethen SG  
Tel. +41 (0) 71 / 747 84 11 Fax. +41 (0) 71 / 747 85 10
- *Further information obtainable from:*  
Product safety department.  
e-mail address: sdb-feyco@feycotreffert.ch
- *1.4 Emergency telephone number:*  
Swiss Toxicological Information Centre  
Emergency telephone: +41 (0)44 251 51 51

## \* SECTION 02: Hazards identification

- *2.1 Classification of the substance or mixture*
- Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 2 - H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 - H319 Causes serious eye irritation.  
STOT SE 3 - H336 May cause drowsiness or dizziness.

- *2.2 Label elements*
- Labelling according to Regulation (EC) No 1272/2008



GHS02



GHS07

- Signal word  
Danger

- Hazard-determining components of labelling:
- ethyl acetate
- Hazard statements  
H225 Highly flammable liquid and vapour.  
H319-EUH066 Causes serious eye irritation. Repeated exposure may cause skin dryness or cracking.  
H336 May cause drowsiness or dizziness.
- Precautionary statements  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.

(continued on page 2)

MATERIAL SAFETY DATA SHEET  
according to 1907/2006/EC, Article 31

**FEYCO  
TREFFERT**

2830809

Reviewed on: 05.09.2016

Printing date: 05.09.2016

**PRODUCT : THINNER V1664 FOR CASANIN WOOD PUTTY**

(continued of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.

- **2.3 Other hazards**
- *Results of PBT and vPvB assessment*
- PBT:  
Not applicable.
- vPvB:  
Not applicable.

\* **SECTION 03: Composition/information on ingredients**

- **3.2 Chemical characterization: Mixtures**
- *Description:*  
Mixture of substances listed below with nonhazardous additions.

- *Dangerous components:*

CAS NO.	Description Index R-phrases	%
*	<b>141-78-6</b> <b>ethyl acetate</b> <b>EC number: 205-500-4</b> <b>Record number 01-2119475103-46</b> ⚠ <b>Flam. Liq. 2 - H225;</b> ⚠ <b>Eye Irrit.</b>	     <b>90,00-100,00</b>
*	<b>2 - H319-EUH066, STOT SE 3 - H336</b>	

**SECTION 04: First aid measures**

- *4.1 Description of first aid measures*
- **After inhalation:**  
Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**  
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. Then consult a doctor.  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**  
Do not induce vomiting; call for medical help immediately.
- **Information for doctor:**
- *4.2 Most important symptoms and effects, both acute and delayed*  
No further relevant information available.
- *4.3 Indication of any immediate medical attention and special treatment needed*  
No further relevant information available.

**SECTION 05: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:**  
Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- *Protective equipment:*  
Mouth respiratory protective device.  
Do not inhale explosion gases or combustion gases.
- **Additional information**  
Cool endangered receptacles with water spray.  
Collect contaminated fire fighting water separately. It must not enter the sewage system.

GB

(continued on page 3)

MATERIAL SAFETY DATA SHEET  
according to 1907/2006/EC, Article 31

FEYCO  
TREFFERT

2830809

Reviewed on: 05.09.2016

Printing date: 05.09.2016

PRODUCT : THINNER V1664 FOR CASANIN WOOD PUTTY

(continued of page 2)

### SECTION 06: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Prevent seepage into sewage system, workpits and cellars.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 07: Handling and storage

- **Handling:**
  - **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.  
Take note of emission threshold.  
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
  - **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
  - **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Store only in the original receptacle.
  - **Information about storage in one common storage facility:**  
Not required.
  - **Further information about storage conditions:**  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)**  
No further relevant information available.

### SECTION 08: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

CAS No.	Designation of material		
141-78-6	ethyl acetate		
<b>WEL</b>			
	<b>Short-term value</b>	<b>400</b>	<b>ppm</b>
	<b>Long-term value</b>	<b>200</b>	<b>ppm</b>

- **Additional information:**  
The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**

(continued on page 4)

MATERIAL SAFETY DATA SHEET  
according to 1907/2006/EC, Article 31

**FEYCO  
TREFFERT**

2830809

Reviewed on: 05.09.2016

Printing date: 05.09.2016

**PRODUCT : THINNER V1664 FOR CASANIN WOOD PUTTY**

(continued of page 3)

- *General protective and hygienic measures:*  
The usual precautionary measures are to be adhered to when handling chemicals.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.  
Do not eat or drink while working.  
Be sure to clean skin thoroughly after work and before breaks.
- *Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Suitable respiratory protective device recommended.*
- *Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Protective gloves Impervious gloves*
- *Material of gloves*  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- *Penetration time of glove material*  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.  
The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.
- *Eye protection: Safety glasses Tightly sealed goggles*
- *Body protection: Protective work clothing*

## SECTION 09: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

#### Appearance:

<b>Form:</b>	Liquid
<b>Colour:</b>	Colourless
<b>Odour:</b>	Characteristic Characteristic
<b>Odour threshold:</b>	Not determined.

#### Change in condition

*	<b>Melting point/Melting range:</b>	-84 °C		
*	<b>Boiling point/Boiling range:</b>	77 °C		
*	<b>Flash point:</b>	-4 °C	c.c.	
*	<b>Flammability (solid, gaseous):</b>	Not applicable.		
*	<b>Ignition temperature:</b>	460 °C		
	<b>Decomposition temperature:</b>	Not determined.		
	<b>Self-igniting:</b>	Not determined.		
	<b>Danger of explosion:</b>	Not determined.		
	<b>Explosion limits:</b>			
	<b>Lower:</b>	2 Vol %		
	<b>Upper:</b>	11 Vol %		
*	<b>Vapour pressure:</b>	at 20 °C	100,000 mbar at	50 °C
		360,000 mbar		
	<b>Density:</b>	0,9000 g/cm <sup>3</sup>		
	<b>Solubility in / Miscibility with water:</b>	at 20 °C	79,00 g/l	
	<b>Viscosity:</b>			
	.	at 20 °C		
*	.	Not determined.		

(continued on page 5)

2830809

Reviewed on: 05.09.2016

Printing date: 05.09.2016

**PRODUCT : THINNER V1664 FOR CASANIN WOOD PUTTY**

(continued of page 4)

**9.2 Other information**

No further relevant information available.

**SECTION 10: Stability and reactivity**

- *10.1 Reactivity*
- *10.2 Chemical stability*
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- *10.3 Possibility of hazardous reactions*  
No dangerous reactions known.
- *10.4 Conditions to avoid*  
No further relevant information available.
- **10.5 Incompatible materials:**  
No further relevant information available.
- **10.6 Hazardous decomposition products:**  
No dangerous decomposition products known.

**SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**
- **Acute toxicity:**
- *LD/LC50 values relevant for classification:*  
**141-78-6 ethyl acetate**  
Oral, LD50: 5620 mg/kg (Rabbit)  
Inhalative, LC50/4h: 1600 mg/l (rat)
- *Primary irritant effect:*
- on the skin:  
No irritant effect.
- on the eye:  
Irritating effect.
- *Sensitization:*  
No sensitising effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant

**SECTION 12: Ecological information**

- *12.1 Toxicity*
- Aquatic toxicity:  
No further relevant information available.
- **12.2 Persistence and degradability**  
No further relevant information available.
- **Behaviour in environmental systems:**
- *12.3 Bioaccumulative potential*  
No further relevant information available.
- 12.4 Mobility in soil  
No further relevant information available.
- **Additional ecological information:**
- *General notes:*  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- **12.5 Results of PBT and vPvB assessment**
- *PBT:*  
Not applicable.
- *vPvB:*  
Not applicable.
- **12.6 Other adverse effects**  
No further relevant information available.

2830809

Reviewed on: 05.09.2016

Printing date: 05.09.2016

PRODUCT : THINNER V1664 FOR CASANIN WOOD PUTTY

(continued of page 5)

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- *European and swiss waste code*

08

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01

wastes from MFSU and removal of paint and varnish

08 01 11

waste paint and varnish containing organic solvents or other dangerous substances

- **Uncleaned packaging:**

- *Recommendation:*

Disposal must be made according to official regulations.

### SECTION 14: Transport information

- **14.1 UN-Number**

ADR

UN1173

IMDG

UN1173

IATA

UN1173

- **14.2 UN proper shipping name**

ADR

1173 ETHYL ACETATE

IMDG

ETHYL ACETATE

IATA

ETHYL ACETATE

- **14.3 Transport hazard class(es)**

ADR

3 Flammable liquids.

Class

Label



IMDG

3 Flammable liquids.

Class

Label



IATA

3 Flammable liquids.

Class

Label



- **14.4 Packing group**

ADR

II

IMDG

II

(continued on page 7)

MATERIAL SAFETY DATA SHEET  
according to 1907/2006/EC, Article 31

**FEYCO  
TREFFERT**

2830809

Reviewed on: 05.09.2016

Printing date: 05.09.2016

**PRODUCT : THINNER V1664 FOR CASANIN WOOD PUTTY**

(continued of page 6)

<b>IATA</b>	II
• <b>14.5 Environmental hazards:</b> Not applicable.	
• <b>14.6 Special precautions for user</b> Warning: Flammable liquids.	
<b>Danger code (Kemler):</b>	33
<b>EMS Number:</b>	F-E,S-D
• <b>14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> Not applicable.	
• <b>Transport/Additional information:</b> Not applicable.	
<b>Excepted quantities (EQ):</b>	E2
<b>Limited quantities (LQ)</b>	1L
<b>Transport category</b>	2
<b>Tunnel restriction code</b>	D/E
<b>IMDG</b>	
<b>Limited quantities (LQ)</b>	1L
<b>Excepted quantities (EQ)</b>	E2
• <b>UN "Model Regulation":</b> UN 1173 ETHYL ACETATE, 3, II	

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **National regulations:**
- **Classification according to VbF:**  
AI
- **Waterhazard class:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:**  
A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- \* • **Relevant phrases**

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
- **Department issuing MSDS:**  
Environment protection department.
- **Abbreviations and acronyms:**  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)

(continued on page 8)

MATERIAL SAFETY DATA SHEET  
according to 1907/2006/EC, Article 31



2830809

Reviewed on: 05.09.2016

Printing date: 05.09.2016

**PRODUCT : THINNER V1664 FOR CASANIN WOOD PUTTY**

*(continued of page 7)*

VbF: Verordnung über brennbare Flüssigkeiten, Österreich (Ordinance on the storage of combustible liquids, Austria)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative